

Fiber Depolarizer (1310nm, 1550nm)

Product Features

- High Extinction Ratio
- Low Insertion Loss
- High Return Loss

Product Applications

- Communication Systems
- Test Instrumentations
- Fiber Sensors
- Research

Specifications

Parameter	Unit	Value
Center Wavelength	nm	1310or 1550
Operating Wavelength Range	nm	±50
Typ. Insertion Loss at 23°C	dB	0.3
Max. Insertion Loss at 23°C	dB	≤0.5
Min. Return loss (input/output)	dB	≥50/50
Typ. Extinction ratio at 23°C	dB	≤3
Max. Optical Power (CW)	mW	500 (Based on proper polarization alignment)
Max. Tensile Load	N	≤5
Fiber Type (Input-output)		PM Panda fiber
package dimensions	mm	Φ5.5*55
Operating Temperature	°C	-5 to +70
Storage Temperature	°C	-40 to +85

* Above specifications are for devices without connectors

* For devices with connectors, IL will be 0.3dB higher, RL will be 5dB lower and ER will be 2dB lower

* The PM fiber and the connector key are aligned to the slow axis

Ordering Information

DEP	Wavelength	Pigtail Type	Fiber Length	Connector
1x1	1310nm 1550nm Specify	250um bare fiber 900um loose tube Specify	0.5m 1m 1.5m 2m Specify	N=None FC/APC FC/UPC SC/APC SC/UPC LC/UPC Specify